
Contents

| | | |
|----------|---|----|
| 1 | Introduction | 1 |
| 1.1 | Some Historical Background | 1 |
| 1.2 | Removal of Particles from Gases | 6 |
| 1.2.1 | Filtration | 8 |
| 1.2.2 | Wet Scrubbers | 10 |
| 1.2.3 | Centrifugal/Cyclonic Devices | 11 |
| 1.2.4 | Knock-out Vessels and Settling Chambers | 12 |
| 1.3 | A Closer Look at Centrifugal Gas Cleaning Devices | 12 |
| 1.3.1 | Applications of Centrifugal Separators | 13 |
| 1.3.2 | Classification of Centrifugal Separators | 17 |
| 1.3.3 | Two Main Classes—Cyclones and Swirl Tubes | 20 |
| 2 | Basic Ideas | 23 |
| 2.1 | Gas Flow | 23 |
| 2.1.1 | Swirling Flow | 23 |
| 2.1.2 | Static and Dynamic Pressure | 26 |
| 2.2 | Particle Motion | 27 |
| 2.3 | Particle Size | 32 |
| 2.3.1 | Definitions of Particle Size | 32 |
| 2.3.2 | Particle Size Distribution | 33 |
| 2.4 | Particle Density | 37 |
| 2.A | Ideal Vortex Laws from N-S Eqs. | 38 |
| 2.B | Model Functions for Size Distributions | 41 |
| 2.B.1 | The Normal Distribution | 42 |
| 2.B.2 | The Log-Normal Distribution | 42 |
| 2.B.3 | The Rosin-Rammler Distribution | 43 |
| 3 | How Cyclones Work | 45 |
| 3.1 | Flow in Cyclones | 45 |
| 3.1.1 | Gas Flow Pattern | 45 |
| 3.1.2 | Particle Flow | 49 |

| | | |
|----------|--|------------|
| 3.2 | Separation Efficiency | 51 |
| 3.2.1 | Overall Separation Efficiency | 51 |
| 3.2.2 | Grade-Efficiency | 51 |
| 3.2.3 | Converting Between Overall Efficiency and Cut-size | 54 |
| 3.3 | Pressure Drop | 54 |
| 3.A | Worked Example: Calculating a Grade-Efficiency Curve | 56 |
| 4 | Cyclone Flow Pattern and Pressure Drop | 59 |
| 4.1 | Discussion | 59 |
| 4.1.1 | Flow Pattern | 60 |
| 4.1.2 | Pressure Drop | 61 |
| 4.2 | Models for the Flow Pattern | 64 |
| 4.2.1 | n-Type Model | 65 |
| 4.2.2 | Barth | 66 |
| 4.3 | Models for the Pressure Drop | 70 |
| 4.3.1 | Models Based on Estimating the Dissipative Loss | 71 |
| 4.3.2 | Core Model | 72 |
| 4.3.3 | Purely Empirical Models | 77 |
| 4.4 | Model Assumptions in Light of CFD and Experiment | 78 |
| 4.5 | Overview | 82 |
| 4.A | Worked Example for Calculating Cyclone Pressure Drop | 83 |
| 4.B | The Meissner and Löffler Model | 85 |
| 5 | Cyclone Separation Efficiency | 89 |
| 5.1 | Discussion | 89 |
| 5.2 | Models | 90 |
| 5.2.1 | Equilibrium-orbit Models: the Model of Barth | 90 |
| 5.2.2 | Time-of-Flight Models | 93 |
| 5.2.3 | Hybrid Models | 96 |
| 5.2.4 | Comparing the Models | 96 |
| 5.3 | Comparison of Model Predictions with Experiment | 97 |
| 5.3.1 | Agreement with Experiment in General | 97 |
| 5.3.2 | A Case Study: the Effect of Cyclone Length | 98 |
| 5.4 | Overview | 102 |
| 5.A | Worked Example, Separation Performance | 103 |
| 5.B | Models of Dietz and of Mothes and Löffler | 106 |
| 6 | The Muschelknautz Method of Modeling | 111 |
| 6.1 | Basis of the Model | 112 |
| 6.2 | Computation of the Inner Vortex Cut-Point, x_{50} | 118 |
| 6.3 | Computation of Efficiency at Low Solids Loadings | 120 |
| 6.4 | Determining if the Mass Loading Effect will Occur | 122 |
| 6.5 | Overall Separation Efficiency when $c_o > c_{oL}$ | 122 |
| 6.6 | Computation of Pressure Drop | 124 |
| 6.A | Example Problems | 125 |

| | | |
|----------|---|-----|
| 6.A.1 | Data from Hoffmann, Peng and Postma (2001) | 125 |
| 6.A.2 | Data from Obermair and Staudinger (2001) | 128 |
| 6.A.3 | Simulation of the Data from Greif (1997) | 129 |
| 6.B | Incorporation of the ‘Inner Feed’ | 133 |
| 7 | Computational Fluid Dynamics | 139 |
| 7.1 | Simulating the Gas Flow Pattern | 140 |
| 7.1.1 | Setting up the Finite Difference Equations | 140 |
| 7.1.2 | Turbulence Models | 142 |
| 7.1.3 | Simulations | 143 |
| 7.2 | Simulating the Particle Flow | 147 |
| 7.2.1 | Eulerian Modeling | 148 |
| 7.2.2 | Lagrangian Particle Tracking | 148 |
| 7.2.3 | 3-D particle tracks | 148 |
| 7.3 | Some Simulations of the Gas and Particle Flow in Cyclones | 149 |
| 7.3.1 | LES Simulations of Derksen and van den Akker | 149 |
| 7.3.2 | Some Remarks on CFD in Cyclones | 160 |
| 7.A | Transport Equations | 161 |
| 8 | Dimensional Analysis and Scaling Rules | 163 |
| 8.1 | Classical Dimensional Analysis | 164 |
| 8.1.1 | Separation Efficiency | 164 |
| 8.1.2 | Pressure Drop | 167 |
| 8.2 | Scaling Cyclones in Practice | 168 |
| 8.2.1 | Approximately Constant Stk_{50} over a Wide Range of Re | 168 |
| 8.2.2 | Eu Only Weakly Dependent on Re | 171 |
| 8.2.3 | Some other Considerations | 172 |
| 8.2.4 | $Stk-Eu$ Relationships | 173 |
| 8.A | Inspecting the Equations of Motion | 176 |
| 8.A.1 | Equation of Motion for the Gas | 176 |
| 8.A.2 | Equation of Motion for a Particle | 176 |
| 8.B | Sample Cyclone Scaling Calculations | 177 |
| 8.B.1 | Inlet Velocity for Re Similarity | 177 |
| 8.B.2 | Prediction from Scale Model | 178 |
| 9 | Other Factors Influencing Performance | 183 |
| 9.1 | The Effect of Solids Loading | 183 |
| 9.1.1 | Effect on Separation Efficiency of Cyclones | 183 |
| 9.1.2 | Models for Effect on Separation Efficiency | 185 |
| 9.1.3 | Effect on the Separation Efficiency of Swirl Tubes | 191 |
| 9.1.4 | Effect on the Pressure Drop of Cyclones | 192 |
| 9.1.5 | Effect on the Pressure Drop Across Swirl Tubes | 194 |
| 9.1.6 | Computing Performance with High Loading | 194 |
| 9.2 | The Effect of the Natural Vortex Length | 195 |
| 9.2.1 | The Nature of the Vortex End | 195 |

| | | |
|-----------|--|------------|
| 9.2.2 | Wall Velocity Due to Core Precession | 197 |
| 9.2.3 | The Significance of the Vortex End | 199 |
| 9.2.4 | Models for the Natural Vortex Length | 203 |
| 9.A | Predicting the Effect of Solids Loading on Cyclone Efficiency .. | 205 |
| 9.B | Predicting the Effect of Loading on Cyclone Pressure Drop .. | 208 |
| 10 | Measurement Techniques | 213 |
| 10.1 | Gas Flow Pattern | 216 |
| 10.2 | Pressure Drop | 218 |
| 10.3 | Particle Flow | 219 |
| 10.4 | Overall Separation Efficiency | 220 |
| 10.4.1 | On-line Sampling of Solids | 221 |
| 10.5 | Grade-Efficiency | 224 |
| 10.5.1 | On-Line <i>vs.</i> Off-Line Size Analysis | 224 |
| 10.5.2 | Sample Capture and Preparation | 225 |
| 10.5.3 | Methods for Size Analysis | 226 |
| 10.A | Estimate of Errors | 231 |
| 11 | Underflow Configurations and Considerations | 235 |
| 11.1 | Underflow Configurations | 235 |
| 11.2 | Importance of a Good Underflow Seal | 239 |
| 11.2.1 | Inleakage Example | 242 |
| 11.3 | Upsets Caused by ‘Too Good’ an Underflow Seal | 243 |
| 11.4 | Second-Stage Dipleg Solids ‘Backup’ | 246 |
| 11.5 | Hopper ‘Crossflow’ | 248 |
| 11.6 | Hopper Venting Options | 250 |
| 11.A | Dipleg Calculation | 253 |
| 11.B | Moment Balance on Flapper Valve Plate | 253 |
| 11.B.1 | Example | 256 |
| 12 | Some Special Topics | 257 |
| 12.1 | Cyclone Erosion | 257 |
| 12.1.1 | Inlet ‘Target Zone’ | 257 |
| 12.1.2 | Lower Cone Section | 260 |
| 12.1.3 | Vortex Tube Outer Surface | 263 |
| 12.1.4 | Erosion Protection | 268 |
| 12.2 | Critical Deposition Velocity | 279 |
| 12.3 | High Vacuum Case | 281 |
| 12.3.1 | Application to Cyclone or Swirl Tube Simulation | 282 |
| 12.A | Worked Example for Critical Deposition Velocity | 283 |
| 12.B | Worked Example with Slip | 283 |

| | |
|---|-----|
| 13 Demisting Cyclones | 287 |
| 13.1 Liquid Creep and ‘Layer Loss’ | 288 |
| 13.2 Demisting Cyclone Design Considerations | 290 |
| 13.3 Some Vapor-Liquid Cyclone Design Geometries and Features | 292 |
| 13.4 Estimating Inlet Drop Size for Two-Phase Mist-Annular Flow | 299 |
| 13.4.1 Estimating Drop Size Distribution | 301 |
| 13.5 Modeling the Performance of Vapor-Liquid Cyclones | 302 |
| 13.5.1 Computation of Cut Size | 302 |
| 13.5.2 Computation of Efficiency at Low Inlet Loadings | 303 |
| 13.6 Criteria for Determining if ‘Mass loading’ (‘Saltation’) Occurs | 303 |
| 13.6.1 Overall Separation Efficiency when $c_o > c_{oL}$ | 304 |
| 13.7 Re-entrainment From Demisting Cyclones | 305 |
| 13.7.1 Re-entrainment Mechanisms and Governing Parameters | 305 |
| 13.7.2 Data for Re-entrainment | 308 |
| 13.A Example Calculations of Droplet Sizes in Pipe Flow | 311 |
| 13.A.1 Finding the Mean Droplet Size | 311 |
| 13.A.2 Finding the Droplet Size Distribution | 312 |
| 13.B Flow Distribution in Parallel Demisting Cyclones | 312 |
| 13.B.1 Calculation of Flow Distribution | 317 |
| 13.B.2 Calculation of Liquid Level Difference | 317 |
| 13.C Method for Estimating Wall Film Thickness and Velocity | 318 |
| 13.C.1 Two-Phase, Co-current, Annular Force Balance, Resolved in the Axial Direction | 320 |
| 13.C.2 Friction Factors and Shear Stresses | 321 |
| 13.C.3 Final Form of Void Fraction Equation | 323 |
| 13.D Example calculation | 324 |
| 14 Foam-Breaking Cyclones | 327 |
| 14.1 Introduction | 327 |
| 14.2 Some Design Considerations and Factors Influencing Behavior | 330 |
| 14.3 Applications | 334 |
| 14.4 Estimating Submergence Required to Prevent Gas ‘Blow Out’ | 334 |
| 14.A Example Calculation of Submergence Required | 340 |
| 15 Design Aspects | 341 |
| 15.1 Cylinder-on-Cone Cyclones with Tangential Inlet | 341 |
| 15.1.1 Some Standard Cyclone Designs | 341 |
| 15.1.2 Design of the Inlet | 342 |
| 15.1.3 Design of the Cone Section | 349 |
| 15.1.4 Solids Outlet Configurations | 350 |
| 15.1.5 Vortex Finder Geometries | 353 |
| 15.1.6 Cyclone Length | 363 |
| 15.1.7 Cyclone Roof | 364 |
| 15.1.8 Cyclone Operating Conditions | 367 |
| 15.2 Design of Swirl Tubes with Swirl Vanes | 368 |

XXVI Contents

| | |
|--|------------|
| 15.2.1 Design of the Inlet Vanes | 368 |
| 15.2.2 Calculation of Inlet ‘Throat’ Area | 370 |
| 15.2.3 Length of the Swirl Tube Body and the Solids Exit | 372 |
| 15.A Example Calculation of the Throat Area | 373 |
| 15.B Construction of Vane “Cut-out” pattern | 374 |
| 16 Multicyclone Arrangements..... | 381 |
| 16.1 Cyclones in Series | 381 |
| 16.2 Cyclones in Parallel..... | 382 |
| 16.A Example Calculation for Multicyclone Arrangements | 391 |
| List of Symbols | 397 |
| List of Tradenames | 403 |
| References | 405 |
| Index | 411 |